

Drainage Dirty Water

BVP - C11

- Automatic mode
- Heavy Duty
- All-purpose vortex pump
- Easy installation
- Cost effective

🇮🇹 Designed in Italy

3
YEAR
WARRANTY



Carry Handle



Diameter Particles
Up To 38 mm



Narrow Holes With
Automatic Mode



	Model	BVP - C11
Electrical data	P2 Power consumption [W]	600
	Voltage [V]	1 ~ 240 AC
	Frequency [Hz]	50
	Current [A]	4.2
	Capacitor nF	12.5
	Capacitor Vc	450
Hydraulic data	Flow rate max. [l/min]	320
	Max. Head [m]	11
	Max. Immersion depth [m]	7
	Low suction capability/automatic mode [mm]	-
	Low suction capability/manual mode [mm]	50
Range of use/materials	Length of Power Cable [m]	10
	Cable	H07 RNF
	Pump International protection	IP X 8
	Insulation Class	F
	Liquid range Temperature [°C]	0 °C / +35 °C
	Dimension of particles [mm]	38
Dimensions / weight	L x W x H [mm]	310 x 250 x 400
	LM [mm]	274
	L1 [mm]	249
	HM [mm]	250
	Discharge Thread BSP	1" 1/2 F
	Box Dimensions l x w x h [cm]	26 x 26 x 42
	Net/Gross Weight [kg]	8.3 / 9.3
	Quantity for pallet [no.]	27

