

# Submersible Pressure Pump BLUEDIVER

- Compact
- Auto on/off Float Switch
- Overheating Protection
- Stainless Steel Filter
- 🇮🇹 Designed in Italy



Adjustable  
Float



Stainless Steel  
Filter



Float



| Model                  | BLUEDIVER C30 A               | BLUEDIVER C40 A |                 |
|------------------------|-------------------------------|-----------------|-----------------|
| Electrical data        | P1 Power consumption [W]      | 900             | 1.100           |
|                        | P2 Pump consumption [W]       | 650             | 750             |
|                        | Voltage [V]                   | 1 ~ 220-240 AC  | 1 ~ 220-240 AC  |
|                        | Frequency [Hz]                | 50              | 50              |
|                        | Current [A]                   | 3.8             | 4.8             |
|                        | Capacitor $\mu$ F             | 12.5            | 12.5            |
|                        | Capacitor Vc                  | 450             | 450             |
|                        | Rated speed [1/min]           | 2.850           | 2.850           |
| Hydraulic data         | Flow rate max. [l/min]        | 95              | 95              |
|                        | Max. Pressure [Bar]           | 3.6             | 4.6             |
|                        | Max. Head [m]                 | 36              | 46              |
|                        | Max. working pressure [bar]   | 6               | 6               |
|                        | Max depth of immersion [m]    | 12              | 12              |
| Range of use/materials | Length of Power Cable [m]     | 15              | 15              |
|                        | Cable                         | H07 RNF         | H07 RNF         |
|                        | Pump International protection | IPX8            | IPX8            |
|                        | Insulation Class              | F               | F               |
|                        | Liquid range Temperature [°C] | 0 °C / +35 °C   | 0 °C / +35 °C   |
|                        | Dimension of particles [mm]   | clean water     | clean water     |
|                        | Max. Ambient Temperature [°C] | +40 °C          | +40 °C          |
| Dimensions / weight    | L x W x H [mm]                | 150 x 150 x 400 | 150 x 150 x 400 |
|                        | DNM GAS                       | 1" F            | 1" F            |
|                        | Box Dimensions l x w x h [cm] | 23 x 19 x 46    | 23 x 19 x 46    |
|                        | Net/Gross Weight [kg]         | 8.7/10          | 9/10.2          |
|                        | Quantity for pallet [no.]     | 40              | 40              |

